

600/1000 V sc Service cables with split concentric neutral & earth conductor Cu Low voltage



Application:

Application	600/1000 V A.C. Service cable
Conductor temperature	Max. 90 °C
Short circuit temperature	Max. 250 °C
Installation temperature	Min. -10 °C
Min. radius of bend	10 x D
Max. pullings tension	Directly on conductor max 50 N/mm ² of total conductor cross section

Construction:

Conductor	Circular stranded copper conductor
Insulation	XLPE
Colour marking of core	Brown
Neutral conductor	Covered copper wires, blue
Earth conductor	Bare, plain copper wires
Outer sheath	PVC, black

Technical:

Standard	BC 7870-3.21 and HD 603 55
Marking of sheath	ELECTRIC CABLE 600/1000 V BS7870-3.21 nkt cables 1 x "Dimension" "Year" "Meters"
Rated voltage	1000 V between phases
Standard length	250 m

Technical properties:

Number of cores and cross-section	Number and diameter of wires in concentric conductor. Neutral.	Number and diameter of wires in concentric conductor. Earth	Insulation thickness	Outer diameter	Approx weight	Standard length	Diameter of drum	Product number
Number x mm ²	Number x mm	Number x mm	mm	mm	kg/km	m	m	
1 x 4	7 x 0,86	3 x 1,38	0,7	10	190	250	0,4	TFX42049
1 x 16	7 x 1,79	4 x 2,27	0,7	15	580	250	0,6	TFX42051
1 x 25	10 x 1,79	4 x 2,27	0,9	17	760	250	0,6	TFX42052

All rights reserved. Any unauthorized usage, redistribution or reproduction of part or all of the content in any form will constitute an infringement of copyright. The data are only indicative and should not be considered a binding representation or warranty from NKT concerning a product's properties or usability. The data page is not exhaustive and should be read in conjunction with NKT other product data sheets, whether published or not. NKT reserves the right to change the data page without prior notice.